

## PENSKY MARTENS FLASH POINT TESTER ASTM D 93 - IP 34 - ISO 2719

The apparatus is a benchtop model which houses the air bath stove and the stirrer motor: differently from other apparatus on the market, our instrument is equipped with a fan that cools down the stove quickly after the test.



- Enamel finished benchtop steel case.
- Cast iron stove, electrically heated with stainless steel external shield.
- Voltage regulator with dial on the front panel.
- Pt100 probe for sample temperature acquisition.
- Digital display for sample temperature, 0.1°C accuracy.
- Oil cup, brass, complete with filling mark. Insulating handle.
- Lid with flame dipping mechanism.
- Electric stirrer, 100 or 250 rpm: switch to select stirrer switch.
- Electric fan for a quick cooling of the stove at the end of the test.
- English written user manual.
- For 220V/50 Hz connections, 900 W power consumption.
- Dimensions (l x w x h): mm 240 x 330 x 450. Weight: 10 kg approximately.
- CE approved.

AD0093-120 Apparatus for ASTM D 93 methods A, B and C and equivalent

#### ACCESSORIES

CAL001 PT100 simulator  
CAL003 Official Certificate for Pt100 simulator

#### CONSUMABLES

AD0093-C00 Oil cup  
AD0093-C01 Lid  
AD0093-C02 PT100 probe  
AD0093-C04 Gas ignitor  
TA009C-N00 ASTM 9C thermometer (-5/+110°C)  
TA010C-N00 ASTM 10C thermometer (+90/+370°C)

Specifications may vary without notice.

**The apparatus includes the items listed aside the picture: accessories etc. should be purchased separately.**



**Dott. Gianni Scavini & C.**

Via Donne della Resistenza, 26 - 28831 Baveno (VB) Italy  
Tel. +39-0323-924134 Fax +39-0323-924935  
www.scavini.com