

PENETRATION

GREASE WORKER

Metal body, screw cover with air valve and thermometer pass, piston with ground-slideway brass handle.

670/MAN MANUAL GREASE WORKER ASTM D217 IP 50 ISO 2137 FTM 791-373

With base with lever

670/AUT AUTOMATIC GREASE WORKER ASTM D217 IP 50 ISO 2137 FTM 791-373

Automatic grease worker machine. Heavy base plate with monofase gear motor preset to make 60 strokes per minute, 6-digit counting mechanism and automatic stroke count and shut-off device. With one grease worker.

Technical specifications:

- Power supply: 230V ±10% 50Hz
- Power: 800W
- Dimensions: 41x30x50 cm
- Weight: 37 kg

670/AUT/2 AUTOMATIC GREASE WORKER 2 POSITIONS ASTM D217 IP 50 ISO 2137 FTM 791-373

With two grease workers.

Technical specifications:

- Power supply: 230V ±10% 50Hz
- Power: 800W

680/¼ ¼ SCALE GREASE WORKER ASTM D1403 IP 310 ISO 2137

8 holes Ø3.17 mm plate, stainless steel

680/½ ½ SCALE GREASE WORKER ASTM D1403 IP 310 ISO 2137

8 holes Ø6.35 mm plate, stainless steel

SPARE PARTS

- | | |
|-----------|------------------------------|
| 15-0681/¼ | PLATE ¼
8 holes Ø3.17 mm. |
| 15-0681/½ | PLATE ½
8 holes Ø6.35 mm. |



ACCESSORIES ON REQUEST

- | | |
|--------------|--|
| 10-0671/ASTM | ASTM WORKER PLATE
With 51 holes Ø6.35 mm, brass nickel-plated |
| 10-0671/FTM | FTM WORKER PLATE
With 270 holes Ø1.58 mm, brass nickel-plated |
| 10-0672 | GREASE CUTTER |
| 10-0673 | OVERFLOW RING |
| T-0672 | BI-METAL THERMOMETER
Range 0 +60°C |

SPARE PARTS

- | | |
|---------|---|
| 15-0670 | GREASE WORKER
Metal body, screw cover with air valve and thermometer pass, piston with ground-slideway brass handle. |
| 15-0672 | AUTOMATIC STROKE COUNT
6 digit |



670/MAN + T-0672

2013

670/AUT

2013