



FLOW TABLES

FOR FLOW AND WORKABILITY TESTS OF MORTAR AND LIME

STANDARDS: EN 459-2, EN 1015-3 / ASTM C230 / *comparable to BS 4551-1


To perform this test, a specimen contained in a cone mould is placed on a metal surface which is then raised and dropped from a known height, after releasing the specimen from the mould.

The equipment consists of a circular top table with spindle, tripod, bronze flow mould and tamper. The apparatuses to EN Standards are equipped also of a filling hopper. Motorized models foresee an automatic digital drop counter.

The flow tables mod. E090 KIT and E090-01 KIT meet to both the EN 459-2 and EN 1015-3 Specifications.

Power supply (motorized models): 230V 1ph 50 Hz 150W

Weight: 25÷60 kg



E090 KIT



E090-01 KIT

ACCESSORIES :

E087-01

FLOW CALLIPER to ASTM and BS Standards, for measuring the diameter of the sample. Brass made.

Weight: 450 g.



E087-01



E086 KIT



E087 KIT



E090-08

E090-08

FLOW CALLIPER to EN 459-2 and EN 1015-3 Specifications.

SPARE PART:

E085-07

FILLING HOPPER to the mould.
Standard: EN 459-2.

Model	Standard	Operated Hand	Motorized	Table dia. mm	Drop height mm	Spare mould	Spare tamper
E086 KIT	ASTM C230 *(BS4551-1)	•		254	12,7	E087-05	E087-06
E087 KIT	ASTM C230 *(BS4551-1)		•	254	12,7	E087-05	E087-06
E090 KIT	EN 459-2 EN 1015-3	•		300	10	E085-05	E085-06
E090-01 KIT	EN 459-2 EN 1015-3		•	300	10	E085-05	E085-06