

## CONCRETE FLOW TABLE

STANDARD: ASTM C124 / comparable to UNI 8020-A / AASHTO T120 / UNE 7102

Used to determine the flow of concrete. The apparatus consists of a flow table, stainless steel flow mould, tamping bar.

C208



C208 + C208-01



MODELS:

**C208** FLOW TABLE

Hand-operated by crank handle.  
Table diameter: 762 mm.  
Weight: 100 kg

**C208-01** MOTORIZATION KIT to be connected to the flow table mod. C208 and to get it automatic. Complete with separate control panel and automatic digital drops counter.  
Power Supply: 230V 1ph 50 Hz 750 W  
Weight: 15 kg

**C214**

**Cementometer**

For the rapid determination of moisture content in wet cement and concrete.

Fast and easy to use; simply insert the prongs into the material being tested,

Accurate and instantaneous readings, digital portable meter.

Ratio range: 0,35 to 0,70 water/cement.

The unit can store over 150 readings.

Data can be recalled via RS-232 interface to using WIN98 and above.

Power: 4AA Batteries

Weight: 2 kg approx.

**C214-01**

**Cementometer**

Same to mod. C214 but with ratio range: 0,25 to 0,5 for low water cement ranges

**Density of hardened concrete**

STANDARDS: EN 12390-7 / BS 812, 1881 :114 / UNI 6394

**V085**

Specific gravity frame. Technical details: see pag. 472

**V085-01**

Cradle for holding specimens

**V041**

Density basket dia. 200 by 200 mm, stainless steel, 3,35 mm mesh size.

Note:

Balances for specific gravity tests: see pag. 470

V072-06



V085

V041



C214