

APPARATUS FOR THE DETERMINATION OF OXIDATION CHARACTERISTICS OF INHIBITED MINERAL OILS ASTM D 943 - IP 157 - ISO 4263, 12205

The apparatus consists of a benchtop steel case containing an aluminium thermostatic block with a series of holes for the introduction of the oxidation cells, a support for the flowmeters and a water dispenser for the condenser refrigeration.



Four-place unit

- Enamel finished benchtop steel case.
- Aluminium block bath with wells for test tubes, 48 mm diameter and 365 mm depth.
- Stainless steel electric heaters.
- Microprocessor thermoregulator with built-in temperature display, 0.1°C accuracy. Probe: PT100 RTD. Regulation accuracy $\pm 0.1^\circ\text{C}$. Working range: from ambient to 100 °C.
- Safety device against overheating.
- Easy access control box placed on the right side of the apparatus and containing all the electronics and electrical parts. Aluminium control panel with english written indications.
- Oxygen inlet manifold with high precision flowmeters with calibration certificate. Individual needle valves for regulating oxygen flow at 3 l/h ± 0.1 l/h
- Water inlet manifold with valve connections for the mushroom condensers.
- Water outlet manifold.
- n° 1 thermometer bracket.
- English written user manual.
- For connection to 220V/50Hz. Power consumption 2000 W.
- CE marked.
- Four, six, eight and twelve-place units available.
- Version with mass flow controllers and software also available.

AD0943-100	Four-place unit. Dimensions (l x w x h): 640 x 430 x 1000 mm. Weight: 90 kg
AD0943-110	Six-place unit. Dimensions (l x w x h): 760 x 430 x 1000 mm. Weight: 110 kg
AD0943-120	Eight-place unit. Dimensions (l x w x h): 640 x 490 x 1000 mm. Weight: 130 kg
AD0943-130	Twelve-place unit. Dimensions (l x w x h): 760 x 430 x 1000 mm. Weight: 160 kg

ACCESSORIES

AD0943-A00	Winding fixture
CAL001	PT100 simulator
CAL003	Official Certificate for Pt100 simulator

CONSUMABLES

AD0943-C00	Test tube
AD0943-C01	Mushroom condenser
AD0943-C02	Oxygen delivery tube
AD0943-C03	Cell thermometer
AD0943-C04	Syringe sampling tube
AD0943-C05	Methacrylate sampling tube holder
AD0943-C06	Sampling tube spacer
AD0943-C07	Catalyst coil
AD0943-C08	Steel wire, 10 m
AD0943-C09	Copper wire, 10 m
TA040C-N00	ASTM 40C thermometer (+72°C/+126°C)

Specifications may vary without notice.

The apparatus includes the items listed aside the picture, accessories etc. should be purchased separately.



Dott. Gianni Scavini & C.

Via Donne della Resistenza, 26 - 28831 Baveno (VB) Italy
Tel. +39-0323-924134 Fax +39-0323-924935
www.scavini.com