

**ASTM D 156 - DIN 51411**

**SCOPE**

Standard Test Method for Saybolt Color of Petroleum Products (Saybolt Chromometer Method).

**SAYBOLT COLOR OF PETROLEUM PRODUCTS**

**- SC CLASSIC -**  
**- REF 941520 -**

**MAIN CHARACTERISTICS**

**SC CLASSIC Normalab Saybolt Chromometer with:**

- ✓ Daylight source built-in the base arranged to project a diffused light up through the tubes
- ✓ 3-position turret assembly (1/2, 1 and 2) with certified Saybolt filters reducing the time required to make a determination and eliminating the handling of the standard filters and the possibility of loss and damage.

**SCOPE OF DELIVERY**


**SC CLASSIC delivered ready for use with:**

- REF 941524** Prismatic eyepiece  
**REF 941525** Matched pair of tubes  
**REF 9415203** Artificial daylight filter with certificate

**ALTERNATIVE FOR WAXES**

**REF 941521 SC CLASSIC WAX**

Same as above but with specific heating tube for petroleum waxes up to 100°C.



**ORDERING INFORMATION**

**REF 941520**  
SC CLASSIC For use on AC 230V - 50Hz - 0.3 A

**REF 941520/115V**  
115 V, 50/60 Hz

(W) 180x (D) 180x (H) 760 mm - (± 8 kg).

CONTACT : [sales@normalab.com](mailto:sales@normalab.com)

NORMALAB FRANCE SAS  
ZA Caux Multipôles 1 - F-76 190 Valliquerville  
Tel. : +33 232 700 100  
Fax : +33 232 704 732

[www.normalab.com](http://www.normalab.com)  
REF 941520 Leaflet 15

DISTRIBUTED BY