

ABEL FLASH POINT TESTER IP 33 - IP 170 – ISO 13736

The apparatus consists of a benchtop case hosting the electrically heated bath. The apparatus is equipped with a 30 rpm electric stirrer with a separate switch.



- Enamel finished steel case.
 - Double wall brass heating bath with hole for water filling.
 - Electric heater with voltage regulator.
 - Pt100 probe for sample temperature acquisition.
 - Digital display for sample temperature, 0.1°C accuracy.
 - One brass cup with handle.
 - One lid with flame exposure device, thermometer well, gas ignitor and pilot flame.
 - 30 rpm electric stirrer with separate switch.
 - English written user manual.
 - For 220 V/50 Hz connection: 500 W power consumption.
- Dimensions (l x w x h): 360 x 360 x 400 mm.
Weight: 12 kg approximately.
CE approved.

IP0170-110 Apparatus

ACCESSORIES

CAL001 PT100 simulator
CAL003 Official Certificate for Pt100 simulator

CONSUMABLES

IP0170-C00 Oil cup
IP0170-C01 Lid
IP0170-C02 PT100 probe
IP0170-C04 Gas ignitor

Specifications may vary without notice.

The apparatus includes the items listed aside the picture, accessories etc. should be purchased separately.



Dott. Gianni Scavini & C.

Via Donne della Resistenza, 26 - 28831 Baveno (VB) Italy
Tel. +39-0323-924134 Fax +39-0323-924935
www.scavini.com