

GREASES

SEPARATION

ASTM D1742 OIL SEPARATION FROM LUBRICATING GREASE DURING STORAGE

This test method covers the determination of the tendency of a lubricating grease to separate oil during storage in both normally filled and partially filled containers

Painted metallic structure with stainless steel level at 4 stand-alone places, inlet stabilizing reducer for low pressures, control manometer for cells, 4 pin valve, air pump, quick connection for additional external source air.

Technical specifications:

- Delivery: 6 l/min
- Operating pressure: 2.4 bar
- Power supply: 230V ±10% 50Hz
- Power: 60W
- Dimensions: 44x35x18 cm
- Weight: 6 kg

2030 GREASES SEPARATION APPARATUS

CONSUMABLES x 2 YEARS

- | | |
|-----------|---|
| 15-2032 | O-RING |
| 15-2031/A | SIEVE STRAINER FOR TEST CELL TYPE "A"
Made of stainless steel 75 µm (200 mesh) |
| 15-2031/B | SIEVE STRAINER FOR TEST CELL TYPE "B"
Made of stainless steel 75 µm (200 mesh) |

SPARE PARTS

- | | |
|-----------|------------------|
| 2460/2030 | AIR PUMP |
| 15-2031 | REDUCER PRESSURE |
| 15-2034 | MANOMETER |

ACCESSORIES ON REQUEST

- | | |
|------------|--|
| 10-2031/A | TEST CELL TYPE "A"
Made of chrome plated copper with a 75 µm (200 mesh) stainless steel sieve strainer for supporting the grease. |
| 10-2031/B | TEST CELL TYPE "B"
Made of aluminum with a 75 µm (200 mesh) stainless steel sieve strainer for supporting the grease. |
| 10-2032 | BEAKER 20 ML, pack of 4 pcs |
| 2470/EL600 | ELECTRONIC BALANCE
Range 600 g., readout 0.01, pan Ø130 |



2030 + 10-2031/A + 10-2031/B

2013